

# Product datasheet

Specifications



## auxiliary contact - NO/NC standard - NS1600b..3200 NS630b..1600

33108

### Main

Product or component type	Auxiliary contact
Device short name	OF
Device application	Breaker status monitoring
Range compatibility	ComPact ComPact NS630b..1600 ComPact ComPact NS1600b..3200
Signal contacts composition	1 NO/NC

### Complementary

Local signalling	ON/OFF indication for open/close
Auxiliary contacts type	Standard
Mounting mode	Clip-on
[Ith] conventional free air thermal current	6 A
Breaking capacity (A)	AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz AC-12: 6 A at 380/440 V AC 50/60 Hz AC-12: 6 A at 480 V AC 50/60 Hz AC-12: 6 A at 660/690 V AC 50/60 Hz AC-15: 6 A at 24 V AC 50/60 Hz AC-15: 6 A at 48 V AC 50/60 Hz AC-15: 5 A at 110 V AC 50/60 Hz AC-15: 4 A at 220/240 V AC 50/60 Hz AC-15: 2 A at 380/440 V AC 50/60 Hz AC-15: 1.5 A at 480 V AC 50/60 Hz AC-15: 0.1 A at 660/690 V AC 50/60 Hz DC-12: 6 A at 24 V DC 50/60 Hz DC-12: 2.5 A at 48 V DC 50/60 Hz DC-12: 0.6 A at 110 V DC 50/60 Hz DC-12: 0.3 A at 220 V DC 50/60 Hz DC-14: 1 A at 24 V DC 50/60 Hz DC-14: 0.2 A at 48 V DC 50/60 Hz DC-14: 0.05 A at 110 V DC 50/60 Hz DC-14: 0.03 A at 220 V DC 50/60 Hz
Minimum load	100 mA at 24 V DC

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 cm
Package 1 Width	6.000 cm
Package 1 Length	10.000 cm
Package 1 Weight	28.000 g

Excluding VAT, FCA Jabal Ali &amp; are subject to change – check with your local distributor.

<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	40
<b>Package 2 Height</b>	15.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	1.324 kg
<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	1280
<b>Package 3 Height</b>	45.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	54.368 kg

## **Contractual warranty**

<b>Warranty (in months)</b>	18
-----------------------------	----



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

## Use Longer

### Lifetime extension

Repair	No
--------	----

## Use Again

### Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins